

# 58mm/80mm (2"/3") Mobile Receipt and Label Printer Bluetooth PPT200BT & PPT300BT

Print receipts and labels on demand and on the go with the PPT200BT and PP300BT mobile printer. This lightweight and compact mobile printer is equipped with key features and is ideal for Direct Store Delivery and Field Sales Automation Applications.



## Features

- Ultra light, compact and portable.
- Rugged design, passed 1.5m drop test.
- Bluetooth 3.0/4.0 Dual Mode.
- Compatible with Android, Windows, WinCE.
- USB charging for your convenience.
- Print most 1D & 2D Barcode.
- Fast printing Speed up to 100mm/s.
- Long-lasting battery life (3 days stand-by).
- Power Saving - Sleep Mode.
- Simple drop-in media loading.
- OLED display.
- MSR option.

## Applications

- Direct Store Delivery.
- Fleet Management.
- Proof of Delivery and Pickup.
- Ticketing.
- Passenger Services.
- Field Sales Automation.
- Field Service.
- Quick and Efficient Checkout.
- Customer Experience.
- Parking Violations

Physical	PPT200BT	PPT300BT
Dimensions	126.9(L) x 84.4(W) x 50.6(H)mm	138.8(L) x 106.3(W) x 61.2(H)mm
Weight	234g (Without paper roll)	475.8g (Without paper roll)
Color	Black and Red	Black and Red
Printing		
Printing Method	Direct Thermal Line Printing	
Resolution	203dpi (8dots/mm)	
Printing Speed	100mm/s	
Printing Width	48mm	
Interface	USB, Bluetooth 3.0/4.0	
Barcode 1D	UPC-A, UPC-E, JAN/EAN8, JAN/EAN13, CODE39, ITF, CODEBAR, CODE128, CODE93	
Barcode 2D	QR code, PDF417	
Graphics	Support bitmap printing with different density and user defined bitmap printing	
Paper		
Paper Type	Continuous paper, black mark paper, linerless label, gap Label	
Paper Width	58mm (2")	80mm (3")
Paper Thickness	0.053~0.1mm	
Paper Roll Diameter	40mm Max	
Paper Loading	Easy loading Mechanism	
Printer Specifications		
Detection Sensors	Paper out detection, Cover open detection, Black mark detection, Gap detection	
Memory	32Mb RAM, 64Mb Flash	
Led Power Indicator	Green	
Led Status Indicator	Blue	
Resident Fonts		
Alphanumeric	ASCII 9x17,9x24, 12x24dots	
User-defined	Yes	
Code Page	48	
Software		
Emulation	ESC/POS	
Driver	Windows XP/Vista/Win7/Win8/Win10/ Linux	
SDK	WinCE, Win Mobile, Android	
Power		
Power Supply Input	AC 100V-240V	
Power Supply Output	DC 5V/2A	
Battery	1400mAh/7.4V rechargeable Li-ion battery	
Power Saving	Sleep Mode	

## Environmental

Operating Temperature -5 °C~ 50 °C

Operating Humidity 25% ~ 85 % RH

Storage Temperature -20°C ~ 70 °C

Storage Humidity 5% ~ 95% RH

## Packaging

In the Box USB Cable, Belt Clip, Paper Roll, Quick Start Guide, CD

Carton Size 17.6cm x 17cm x 5cm 21.6cm x 16.6cm x 7.4cm

Gross Weight(kg) 0.50Kg. 0.67Kg.

## Options

Docking Cradle, MSR

Warranty 1 year



[www.3nstar.com](http://www.3nstar.com)