



4" Direct Thermal Label Printer

LDT104

The LDT104 Label printer offers professional printing for any budget. It's affordable, easy-to-use making it ideal for a variety of labeling applications. Although value priced, this printer is engineered for reliability and longevity. The LDT104 has a dual-wall framed construction and all-metal printhead to reduce replacement parts and decrease printer downtime.



Features

- 5 IPS high printing speed
- TSPL Emulation (EPL, ZPL, DPL)
- 8MB SDRAM, 4MB Flash
- 203 dpi resolution
- Double-walled clamshell design
- Bartender Label Printing Software

Physical	
Dimensions	190 mm (W) × 220 mm (D)× 182 mm (H)
Weight	1.40Kg.
Color	Black
Printing	
Printing Method	Direct Thermal
Printing Speed	127 mm (5")/S
Resolution	8 dots/mm(203DPI)
Max Printing Width	108 mm (4.25")
Max Printing length	2286 mm (90")
Media Specifications	
Media Type	Continuous, gap, black mark, fan-fold and punched hole
Media Width	20-112mm (0.78"-4.4")
Media Thickness	0.06~0.16mm (0.0236"~0.063")
Label length	10~2, 286mm(0.4"~90")
Label Roll Diameter	127 mm (5")
Label Roll Core	24.5mm (1") min
Paper Supply Method	Drop-in Paper Load
Features	
Sensor	Black mark reflective sensor, Cover open sensor, Gap sensor
Memory	4MB Flash Memory, 8MB SDRAM, SD card reader for Flash memory expansion up to 4 GB
Interface	USB 2.0
Software	
Emulation	TSPL (EPL, ZPL, DPL)
Driver	Win 7/Win 8/Win 10
1D Barcode Printing	Code 39, Code 93, Code 128UCC, Code 128 subsets A, B, C, Codabar, Interleaved 2 of 5, EAN-8, EAN-13,EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China POST
2D Barcode Printing	MaxiCode, PDF417, Data matrix, QR Code
Font and barcode rotation	0°、 90°、 180°、 270°
Electrical	
Power Supply Input	AC 110V/220V, 50~60Hz (Adapter)
Power Supply Output	DC 24V/2.5A
EMC	FCC, CE, CCC, CB, RoHS
Environmental	
Operating Temperature	5°C to 40°C
Storage Temperature	-40° to 60°C
Humidity	25~85% non-condensing
Storage Humidity	10 ~ 90% non-condensing
Packaging	
In the Box	Windows labeling software, Driver and user manual CD, Quick start guide, USB cable, Power cord, External switching power adapter
Carton Size	230 mm (W) × 330 mm (D)× 240 mm (H)
Gross Weight	2.35Kg.
Warranty	1 Year

