

Thermal Receipt Printer

RPT008

RPT008 Thermal Receipt Printer offers affordability, reliability and stylist design, build with high end stainless steel frame, top quality mechanism and easy to configure.

It features fast printing up to 260mm/s, Serial, USB and LAN. Supports mobile operating systems Windows and Linux



Features

- 260mm/s high speed printing.
- Support QR code printing.
- Serial + USB + LAN interface.
- Support receipt coming and error alarm.'
- ESC/POS Command Support.
- Eight levels printing density.
- Support 2048KB input buffer.
- Printer status monitoring.
- Easy paper loading Structure Design.

Physical

Dimensions (LxWxH)	180mm x 140mm x 135mm
Weight	1.1 kgs.
Gross Weight	2.0 kgs.
Color	Black

Electrical

Power Supply (Adapter)	Input: AC 110V/220V,50~60Hz Output: DC 24V/2.5A
------------------------	---

Environmental

Operating Temperature	0°C to 45°C, humidity (10~80%)
Storage Temperature	-10° to 60°C humidity (10~90%)

Performance

Printing Method	Direct Thermal
Printing Speed	260mm/s
Resolution	8 dots/mm, 576 dots/line
Effective Printing Width	76mm (2.9")
Media Type	Thermal Paper
Paper Width	79.5±0.5mm
Paper Roll Diameter	80mm (3.1"),(Max)
Paper Supply Method	Drop-in Paper Load
Paper Thickness	0.06mm-0.08mm
Print Head	150 km
Barcodes	UPC-A, UPC-E, EAN-13, EAN-8, CODE39, ITF, CODABAR, CODE 39, CODE93, CODE128
2D Code	QR Code, PDF417
Driver	Win 2000/Win 2003/Win NT/Win XP/Win Vista/win 7/Win 8/Win 8.1/ Linux
Sensor	Paper end sensor, error alarm sensor, cover open sensor, Order coming alarm, Reprint function
Drawer Port	1 Port - DC 24V
Interface	RS-232, USB and Ethernet
Memory	NV Flash 256K, Input Buffer 2048K
Auto Cutter Type	Guillotine
Auto Cutter Life	1,500,000 cuts
Emulation	ESC/POS
Warranty	1 year

