

## Touch Screen Self Service

K32 Series kiosk is a computer terminal featuring specialized hardware that provides access to information and applications for communication, commerce, entertainment, or education.

The K32 has been designed for retail, food service and hospitality to improve customer service. Interactive kiosks are typically placed in high foot traffic settings such as fast foods, shops, hotel lobbies or airports.

Integration of technology allows kiosks to perform a wide range of functions, evolving into self-service kiosks. For example, kiosks may enable users to order from a shop's catalogue when items are not in stock, check out a library book, look up information about products, place a food order or enter a public utility bill account number in order to perform an online transaction. Customized components such as card readers, barcode scanners and thermal printers enable K32 to meet the owner's specialized needs.



### **Features**

- 32" 10 points Capacitive Touch Screen Monitor
- Floor Standing or Wall Mount capable
- Core i5-4200 4th Generation
- Built-in 1D/2D barcode scanner
- 80mm (3") thermal printer with Auto cutter
- Payment Terminal Slot
- Thin body easy to adapt to any environment
- Built-in Wi-fi - Dual Antenna
- Front Camera

<b>Physical</b>	
Construction	Paint coat steel
Color	Black and Silver
Dimensions	1040mm x 466mm x 200mm
Weight	Terminal Body: 25.8Kg. Stand: 6.2Kg. Pedestal: 14.8Kg.
<b>Performance</b>	
CPU	Intel Core i5-4200U, 4th Generation
Memory	4GB RAM Expandable to 8GB
Storage	120 GB SSD (mSATA)
<b>Connectivity</b>	
Wi-Fi	Dual Band 802.11ac, a/b/g, n
Bluetooth	4.0
Ethernet	10/100/1000M RJ45
USB	1 USB 3.0, 3 USB 2.0
RS232	1 COM RS232
VGA output	1 VGA
Audio output	3.5mm earphone
Audio Input	Microphone (Combo 3.5")
<b>Operating system</b>	
Versions	Windows 7 32-bit/64-bit, Windows 10 32-bit/64-bit
<b>Touch Panel</b>	
Touchscreen type	10 Points Capacitive
Transmittance	>95%
Touch times	>100,000,000
<b>Monitor</b>	
Type	32" TFT LCD, LED Backlight
Resolution	1920 * 1080
Pixel	0.36375 (H) x 0.36375(W)
Brightness (Typical)	300 cd/m <sup>2</sup>
Contrast Ratio	4000:1(Typical) 3000:1(Min)
Response Time	6.5ms
Viewing Angle	150°
Color Support	16.7M
Hor. Frequency	60KHz(Min.)/67.5KHz(Typ.)/73KHz(MAX)
Ver. Frequency	47Hz(Min.)/60Hz(Typ.)/63Hz(MAX)
Bandwidth	60Hz
Life time	>100,000 hours
<b>Peripheral</b>	
Printer	80mm Thermal, USB, 170mm/s, Auto cutter
Scanner	1D/2D 5mil, USB

## Power Supply

Power Consumption	60W display/60W for printer
Adapter Output	DC 12V/5A, 24V/2.5A
Adapter Input	AC 100-240V, 50-60HZ

## Environmental

Operating Temperature	0°C to 40°C
Operating Humidity	10% to 90%
Storage Temperature	-10°C to 40°C
Storage Humidity	10% to 90%
Sealing	IP45

In the box	<ol style="list-style-type: none"><li>1.Self-service terminal body</li><li>2.Metal Pillar</li><li>3.Metal Base</li><li>4.Wall-mount bracket</li><li>5.AC adaptor</li><li>6.CD disk</li><li>7.Manual</li><li>8.Bolts</li></ol>
------------	---

## Packaging

Carton Size	Terminal Body: 1205mm x 610mm x 240mm Stand: 1070mm x 267mm x 108mm Pedestal: 530mm x 480mm x 93mm
Gross Weight(kg)	Terminal Body: 26.6Kg. Stand: 6.7Kg. Pedestal: 15.5Kg.

## Options

Wall Mount Kit

Stand

4G

**Warranty** **1 Year**

