

# 4" Direct Thermal Label Printer LDT114

The LDT114 Label printer offers professional printing for any budget. It's affordable, easy-to-use making it ideal for a variety of labeling applications. Although value priced, this printer is engineered for reliability and longevity.

The LDT114 has a dual-wall framed construction and all-metal print head to reduce replacement parts and decrease printer downtime.



## Features:

---

- 6 IPS high printing speed
- TSPL Emulation (EPL, ZPL, DPL)
- 8MB SDRAM, 8MB Flash. Micro SD Card Reader for Flash Memory Expansion
- 203 dpi resolution.
- Double-walled clamshell design
- Bartender Label Printing Software
- USB and Ethernet Interface

<b>Physical</b>	
Dimensions	215 mm (W) × 178 mm (D)× 155 mm (H)
Weight	1.31Kg.
Color	Black
<b>Printing</b>	
Printing Method	Direct Thermal
Printing Speed	152mm/S (6 IPS)
Resolution	8 dots/mm(203DPI)
Max Printing Width	108 mm (4.25")
Max Printing length	1778 mm (70")
<b>Media Specifications</b>	
Media Type	Continuous, gap, black mark, fanfold and punched hole
Media Width	20-115mm (0.78"-4.5")
Media Thickness	0.06~0.25mm (0.0236" ~ 0.063")
Label length	10~1,778mm (0.4" ~ 70")
Label Roll Diameter	127 mm (5")
Label Roll Core	24.5mm (1") min
<b>Features</b>	
Sensor	Black mark reflective sensor, Cover open sensor, Gap sensor
Memory	8MB Flash Memory, 8MB SDRAM, Micro SD card reader for Flash memory expansion, up to 4 GB
Interface	USB 2.0 & Ethernet
<b>Software</b>	
Emulation	TSPL, EPL, ZPL, DPL
Compatibility	Windows, Linux, Android, Mac OS, iOS
1D Barcode Printing	Code 39, Code 93, Code 128UCC, Code 128, subsets A, B, C, Codabar, Interleaved 2 of 5, EAN-8,EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China POST, GS1 DataBar, Code11
2D Barcode Printing	PDF-417, Maxicode, DataMatrix, QR code, Aztec
Font and barcode rotation	0°, 90°, 180°, 270°
<b>Electrical</b>	
Power Supply Input	AC 110V/220V, 50~60Hz (Adapter)
Power Supply Output	DC 24V/2.5A
EMC	FCC, CE, CCC, CB
<b>Environmental</b>	
Operating Temperature	-10°C to 50°C (14 ~ 122 °F)
Operating Humidity	10 ~ 90% non-condensing
Storage Temperature	-40° to 60°C (-40 ~ 140 °F)
Storage Humidity	10 ~ 90% non-condensing
<b>Packaging</b>	
In the Box	Windows labeling software driver and user manual CD, Quick start guide, USB cable, Power cord, External switching power adapter
Box Dimension	220 mm (W) × 325 mm (D)× 196 mm (H)
Gross Weight	2.32Kg.
Warranty	1 Year

