

4" Direct Thermal Label Printer LDT114

The LDT114 Label printer offers professional printing for any budget. It's affordable, easy-to-use making it ideal for a variety of labeling applications. Although value priced, this printer is engineered for reliability and longevity.

The LDT114 has a dual-wall framed construction and all-metal print head to reduce replacement parts and decrease printer downtime.



Features:

- 6 IPS high printing speed
- TSPL Emulation (EPL, ZPL, DPL)
- 8MB SDRAM, 8MB Flash. Micro SD Card Reader for Flash Memory Expansion
- 203 dpi resolution.
- Double-walled clamshell design
- Bartender Label Printing Software

Physical	
Dimensions	215 mm (W) × 178 mm (D)× 155 mm (H)
Weight	1.31Kg.
Color	Black
Printing	
Printing Method	Direct Thermal
Printing Speed	152mm/S (6 IPS)
Resolution	8 dots/mm(203DPI)
Max Printing Width	108 mm (4.25")
Max Printing length	1778 mm (70")
Media Specifications	
Media Type	Continuous, gap, black mark, fan-fold and punched hole
Media Width	20-115mm (0.78"-4.5")
Media Thickness	0.06~0.25mm (0.0236" ~ 0.063")
Label length	10~1,778mm (0.4" ~ 70")
Label Roll Diameter	127 mm (5")
Label Roll Core	24.5mm (1") min
Features	
Sensor	Black mark reflective sensor, Cover open sensor, Gap sensor
Memory	8MB Flash Memory, 8MB SDRAM, Micro SD card reader for Flash memory expansion, up to 4 GB
Interface	USB 2.0 & Lan
Software	
Emulation	TSPL, EPL, ZPL, DPL
Driver	Win 7/Win 8/Win 10
1D Barcode Printing	Code 39, Code 93, Code 128UCC, Code 128, subsets A, B, C, Codabar, Interleaved 2 of 5, EAN-8,EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China POST, GS1 DataBar, Code11
2D Barcode Printing	PDF-417, Maxicode, DataMatrix, QR code, Aztec
Font and barcode rotation	0°, 90°, 180°, 270°
Electrical	
Power Supply Input	AC 110V/220V, 50~60Hz (Adapter)
Power Supply Output	DC 24V/2.5A
EMC	FCC, CE, CCC, CB
Environmental	
Operating Temperature	-10°C to 50°C (14 ~ 122 °F)
Operating Humidity	10 ~ 90% non-condensing
Storage Temperature	-40° to 60°C (-40 ~ 140 °F)
Storage Humidity	10 ~ 90% non-condensing
Packaging	
In the Box	Windows labeling software driver and user manual CD, Quick start guide, USB cable, Power cord, External switching power adapter
Box Dimension	220 mm (W) × 325 mm (D)× 196 mm (H)
Gross Weight	2.32Kg.
Warranty	1 Year

