



Mobile Receipt and Label Printer 80mm (3") PPT305

Print receipts and labels on demand and on the go with the PPT305 mobile printer.

This lightweight and compact mobile printer is equipped with key features and is ideal for Direct Store Delivery and Field Sales Automation Applications.









Features:

- Ultra-light, compact and portable
- Rugged design, 1.5m (5') drop resistance
- Bluetooth and USB Interface
- Compatible with Android, Windows, Linux, Mac OS

- USB charging Type C
- Print most 1D & 2D Barcode
- Long-lasting battery life
- Power Saving Sleep Mode
- OLED Screen
- Simple drop-in media loading

Physical	
Color	Black and Red
Printer Dimension	124(L) x 108(W) x 61(H)mm
Net Weight	0.357Kg
Printing	
Printing Method	Direct Thermal
Printing Speed	70mm/s
Resolution	203dpi (8dots/mm)
Max Printing Width	72mm
Paper Specifications	
Media Type	Continuous paper, black mark paper, gap Label
Paper Width	20mm - 80mm
Paper Thickness	0.06mm - 0.254mm
Paper Roll Diameter	50mm (Max)
Paper Supply Method	Drop-in
Features	
Sensor	Paper out detection, Cover open detection, Black mark
	detection, Gap detection
Memory	8MB RAM, 8MB Flash
Print Head Life	30Km
Interface	Bluetooth
Software	
Emulation	TSPL, EPL, ZPL, DPL, CPCL, ESC/POS
Compatibility	Android, Windows, Linux, Mac OS
1D Barcode Printing	Code128 subsets A.B.C,Code128UCC, EAN128, Interleave 2
1D Barcode Printing	of 5, Code 39,Code 93,EAN-13, EAN-8, Codabar, POSTNET,
1D Barcode Printing	of 5, Code 39,Code 93,EAN-13, EAN-8, Codabar, POSTNET, UPC-A, UPC-E, EAN and UPC 2(5) digits, MSI, PLESSEY, China
1D Barcode Printing	of 5, Code 39,Code 93,EAN-13, EAN-8, Codabar, POSTNET, UPC-A, UPC-E, EAN and UPC 2(5) digits, MSI, PLESSEY, China Post, ITF14, EAN14, Code 11, TELPEN, PLANET, Code 49,
U	of 5, Code 39,Code 93,EAN-13, EAN-8, Codabar, POSTNET, UPC-A, UPC-E, EAN and UPC 2(5) digits, MSI, PLESSEY, China Post, ITF14, EAN14, Code 11, TELPEN, PLANET, Code 49, Deutsche Post Identcode, Deutsche Post Leitcode, LOGMARS
2D Barcode Printing	of 5, Code 39,Code 93,EAN-13, EAN-8, Codabar, POSTNET, UPC-A, UPC-E, EAN and UPC 2(5) digits, MSI, PLESSEY, China Post, ITF14, EAN14, Code 11, TELPEN, PLANET, Code 49,
2D Barcode Printing Electrical	of 5, Code 39,Code 93,EAN-13, EAN-8, Codabar, POSTNET, UPC-A, UPC-E, EAN and UPC 2(5) digits, MSI, PLESSEY, China Post, ITF14, EAN14, Code 11, TELPEN, PLANET, Code 49, Deutsche Post Identcode, Deutsche Post Leitcode, LOGMARS DataMatrix, Maxicode, PDF-417, QR code
2D Barcode Printing Electrical Power Supply Input	of 5, Code 39,Code 93,EAN-13, EAN-8, Codabar, POSTNET, UPC-A, UPC-E, EAN and UPC 2(5) digits, MSI, PLESSEY, China Post, ITF14, EAN14, Code 11, TELPEN, PLANET, Code 49, Deutsche Post Identcode, Deutsche Post Leitcode, LOGMARS DataMatrix, Maxicode, PDF-417, QR code AC 110V-240V, 50/60Hz (Adapter)
2D Barcode Printing Electrical Power Supply Input Power Supply Output	of 5, Code 39,Code 93,EAN-13, EAN-8, Codabar, POSTNET, UPC-A, UPC-E, EAN and UPC 2(5) digits, MSI, PLESSEY, China Post, ITF14, EAN14, Code 11, TELPEN, PLANET, Code 49, Deutsche Post Identcode, Deutsche Post Leitcode, LOGMARS DataMatrix, Maxicode, PDF-417, QR code AC 110V-240V, 50/60Hz (Adapter) DC 5V/2A
2D Barcode Printing Electrical Power Supply Input Power Supply Output Battery	of 5, Code 39,Code 93,EAN-13, EAN-8, Codabar, POSTNET, UPC-A, UPC-E, EAN and UPC 2(5) digits, MSI, PLESSEY, China Post, ITF14, EAN14, Code 11, TELPEN, PLANET, Code 49, Deutsche Post Identcode, Deutsche Post Leitcode, LOGMARS DataMatrix, Maxicode, PDF-417, QR code AC 110V-240V, 50/60Hz (Adapter) DC 5V/2A 2500mAh / 7.2V rechargeable Li-ion battery
2D Barcode Printing Electrical Power Supply Input Power Supply Output Battery Power Saving	of 5, Code 39,Code 93,EAN-13, EAN-8, Codabar, POSTNET, UPC-A, UPC-E, EAN and UPC 2(5) digits, MSI, PLESSEY, China Post, ITF14, EAN14, Code 11, TELPEN, PLANET, Code 49, Deutsche Post Identcode, Deutsche Post Leitcode, LOGMARS DataMatrix, Maxicode, PDF-417, QR code AC 110V-240V, 50/60Hz (Adapter) DC 5V/2A
2D Barcode Printing Electrical Power Supply Input Power Supply Output Battery Power Saving Environmental	of 5, Code 39,Code 93,EAN-13, EAN-8, Codabar, POSTNET, UPC-A, UPC-E, EAN and UPC 2(5) digits, MSI, PLESSEY, China Post, ITF14, EAN14, Code 11, TELPEN, PLANET, Code 49, Deutsche Post Identcode, Deutsche Post Leitcode, LOGMARS DataMatrix, Maxicode, PDF-417, QR code AC 110V-240V, 50/60Hz (Adapter) DC 5V/2A 2500mAh / 7.2V rechargeable Li-ion battery Sleep Mode
2D Barcode Printing Electrical Power Supply Input Power Supply Output Battery Power Saving Environmental Operating Temperature	 of 5, Code 39,Code 93,EAN-13, EAN-8, Codabar, POSTNET, UPC-A, UPC-E, EAN and UPC 2(5) digits, MSI, PLESSEY, China Post, ITF14, EAN14, Code 11, TELPEN, PLANET, Code 49, Deutsche Post Identcode, Deutsche Post Leitcode, LOGMARS DataMatrix, Maxicode, PDF-417, QR code AC 110V-240V, 50/60Hz (Adapter) DC 5V/2A 2500mAh / 7.2V rechargeable Li-ion battery Sleep Mode 5°C to 40°C
2D Barcode Printing Electrical Power Supply Input Power Supply Output Battery Power Saving Environmental Operating Temperature Operating Humidity	 of 5, Code 39,Code 93,EAN-13, EAN-8, Codabar, POSTNET, UPC-A, UPC-E, EAN and UPC 2(5) digits, MSI, PLESSEY, China Post, ITF14, EAN14, Code 11, TELPEN, PLANET, Code 49, Deutsche Post Identcode, Deutsche Post Leitcode, LOGMARS DataMatrix, Maxicode, PDF-417, QR code AC 110V-240V, 50/60Hz (Adapter) DC 5V/2A 2500mAh / 7.2V rechargeable Li-ion battery Sleep Mode 5°C to 40°C 10% ~ 90% RH
2D Barcode Printing Electrical Power Supply Input Power Supply Output Battery Power Saving Environmental Operating Temperature Operating Humidity Storage Temperature	 of 5, Code 39,Code 93,EAN-13, EAN-8, Codabar, POSTNET, UPC-A, UPC-E, EAN and UPC 2(5) digits, MSI, PLESSEY, China Post, ITF14, EAN14, Code 11, TELPEN, PLANET, Code 49, Deutsche Post Identcode, Deutsche Post Leitcode, LOGMARS DataMatrix, Maxicode, PDF-417, QR code AC 110V-240V, 50/60Hz (Adapter) DC 5V/2A 2500mAh / 7.2V rechargeable Li-ion battery Sleep Mode 5°C to 40°C 10% ~ 90% RH -40° to 60°C
2D Barcode Printing Electrical Power Supply Input Power Supply Output Battery Power Saving Environmental Operating Temperature Operating Humidity Storage Temperature Storage Humidity	 of 5, Code 39,Code 93,EAN-13, EAN-8, Codabar, POSTNET, UPC-A, UPC-E, EAN and UPC 2(5) digits, MSI, PLESSEY, China Post, ITF14, EAN14, Code 11, TELPEN, PLANET, Code 49, Deutsche Post Identcode, Deutsche Post Leitcode, LOGMARS DataMatrix, Maxicode, PDF-417, QR code AC 110V-240V, 50/60Hz (Adapter) DC 5V/2A 2500mAh / 7.2V rechargeable Li-ion battery Sleep Mode 5°C to 40°C 10% ~ 90% RH
2D Barcode Printing Electrical Power Supply Input Power Supply Output Battery Power Saving Environmental Operating Temperature Operating Humidity Storage Temperature Storage Humidity Packaging	of 5, Code 39,Code 93,EAN-13, EAN-8, Codabar, POSTNET, UPC-A, UPC-E, EAN and UPC 2(5) digits, MSI, PLESSEY, China Post, ITF14, EAN14, Code 11, TELPEN, PLANET, Code 49, Deutsche Post Identcode, Deutsche Post Leitcode, LOGMARS DataMatrix, Maxicode, PDF-417, QR code AC 110V-240V, 50/60Hz (Adapter) DC 5V/2A 2500mAh / 7.2V rechargeable Li-ion battery Sleep Mode 5°C to 40°C 10% ~ 90% RH -40° to 60°C 10% ~ 90% RH
2D Barcode Printing Electrical Power Supply Input Power Supply Output Battery Power Saving Environmental Operating Temperature Operating Humidity Storage Temperature Storage Humidity Packaging In the Box	 of 5, Code 39,Code 93,EAN-13, EAN-8, Codabar, POSTNET, UPC-A, UPC-E, EAN and UPC 2(5) digits, MSI, PLESSEY, China Post, ITF14, EAN14, Code 11, TELPEN, PLANET, Code 49, Deutsche Post Identcode, Deutsche Post Leitcode, LOGMARS DataMatrix, Maxicode, PDF-417, QR code AC 110V-240V, 50/60Hz (Adapter) DC 5V/2A 2500mAh / 7.2V rechargeable Li-ion battery Sleep Mode 5°C to 40°C 10% ~ 90% RH -40° to 60°C 10% ~ 90% RH USB Type C Cable, Quick Start Guide, CD
2D Barcode Printing Electrical Power Supply Input Power Supply Output Battery Power Saving Environmental Operating Temperature Operating Humidity Storage Temperature Storage Humidity Packaging In the Box Box Dimension	of 5, Code 39,Code 93,EAN-13, EAN-8, Codabar, POSTNET, UPC-A, UPC-E, EAN and UPC 2(5) digits, MSI, PLESSEY, China Post, ITF14, EAN14, Code 11, TELPEN, PLANET, Code 49, Deutsche Post Identcode, Deutsche Post Leitcode, LOGMARS DataMatrix, Maxicode, PDF-417, QR code AC 110V-240V, 50/60Hz (Adapter) DC 5V/2A 2500mAh / 7.2V rechargeable Li-ion battery Sleep Mode 5°C to 40°C 10% ~ 90% RH -40° to 60°C 10% ~ 90% RH USB Type C Cable, Quick Start Guide, CD 180(L) x 160(W) x 80(H)mm
2D Barcode Printing Electrical Power Supply Input Power Supply Output Battery Power Saving Environmental Operating Temperature Operating Humidity Storage Temperature Storage Temperature Storage Humidity Packaging In the Box Box Dimension Gross Weight	 of 5, Code 39,Code 93,EAN-13, EAN-8, Codabar, POSTNET, UPC-A, UPC-E, EAN and UPC 2(5) digits, MSI, PLESSEY, China Post, ITF14, EAN14, Code 11, TELPEN, PLANET, Code 49, Deutsche Post Identcode, Deutsche Post Leitcode, LOGMARS DataMatrix, Maxicode, PDF-417, QR code AC 110V-240V, 50/60Hz (Adapter) DC 5V/2A 2500mAh / 7.2V rechargeable Li-ion battery Sleep Mode 5°C to 40°C 10% ~ 90% RH -40° to 60°C 10% ~ 90% RH USB Type C Cable, Quick Start Guide, CD 180(L) x 160(W) x 80(H)mm 0.75Kg.
2D Barcode Printing Electrical Power Supply Input Power Supply Output Battery Power Saving Environmental Operating Temperature Operating Humidity Storage Temperature Storage Humidity Packaging In the Box Box Dimension	of 5, Code 39,Code 93,EAN-13, EAN-8, Codabar, POSTNET, UPC-A, UPC-E, EAN and UPC 2(5) digits, MSI, PLESSEY, China Post, ITF14, EAN14, Code 11, TELPEN, PLANET, Code 49, Deutsche Post Identcode, Deutsche Post Leitcode, LOGMARS DataMatrix, Maxicode, PDF-417, QR code AC 110V-240V, 50/60Hz (Adapter) DC 5V/2A 2500mAh / 7.2V rechargeable Li-ion battery Sleep Mode 5°C to 40°C 10% ~ 90% RH -40° to 60°C 10% ~ 90% RH USB Type C Cable, Quick Start Guide, CD 180(L) x 160(W) x 80(H)mm



