

All-in-One i5 11th Generation POS System **PTE0211**

The 3nStar All-in-One PTE0211 has been designed for Point of Sale and Hospitality applications.

It is robust, dust resistant and capable of continuous operation 24 hours a day, 365 days a year.



Features:

- 15" Capacitive Multitouch Touch Screen: Provides a brighter image and a more sensitive touch.
- Industrial Motherboard with Intel Core i5 11th Generation: efficient and reliable.
- 8GB RAM expandable up to 32GB.
- Solid Stage 240GB Hard Drive expandable to 1TB provides best performance, reliability and durability.
- Dual Band 802.11ac, a/b/g, n Wi-Fi: Connect effortlessly without wires.
- Bluetooth 4.0: Easy pairing with all your devices (BT Scanners, Mobile Printers, keyboard).
- Rich I/O: 7 USB, 2 RS232, 1 VGA, and 1HDMI
- Optional Customer Display 9.7" LCD for better customer interaction
- Support PXE (Preboot Execution Environment) that allows to be configured and booted remotely by an administrator
- Compatible with most versions of Windows and Linux

Physical	
Dimensions	400mm x 360mm x 210mm
Weight	6.3Kg.
Construction	ABS Plastic and Galvanized Steel
Color	Silvery around the body
Performance	
Operating system	(Optional) Windows and Linux
CPU	Intel Core i5 6 th Generation
Memory	8GB DDR4 expandable to 32GB
Storage	240GB SSD expandable to 1TB
Connectivity	
Wi-Fi	Double Band 802.11ac, a/b/g, n
Bluetooth	4.0
Ethernet	10/100/1000M RJ45
USB	7 Ports
Serial RS232	2 Ports DB9
Video Output	2 Ports (1 VGA, 1 HDMI)
Touch Panel	
Touchscreen type	Capacitive 10 points
Transmittance	>95%
Touch times	More than 50,000,000
Monitor	
Resolution	1024 * 768
Pixel	0.297(V)×0.297(H)mm
Brightness (Typical)	400 cd/m ²
Contrast Ratio	800:1(Typical) 450:1(Min)
Response Time	16ms
Viewing Angle	150°/140°
Color Support	16,2M
Horizontal Frequency	60Khz.
Vertical Frequency	78Hz
Bandwidth	60Hz
Lifetime	More than 50,000 Hours
Electrical	
Adapter Output	DC 12V, 7.5A
Adapter Input	Adapter AC 100-240V, 50-60HZ

Environmental	
Operating Temperature	0°C ~ 50°C
Storage Temperature	-20°C ~ 60°C
Humidity	10% ~ 90% (without condensation)
Packaging	
In the Box	AC Adapter and Manual
Carton Size	320mm x 480 mm x 460mm
Gross Weight(kg)	9.5Kg
Certifications and Warranty	
Certifications	CE, ROHS, FCC, CCC
Warranty	1 year (Extended Warranty Available)

Accesorios:

USB Magnetic Stripe
Reader 3 Tracks
PTE0105-MSR



9.7" Customer LCD
Customer Display
PTE0105-M10

