

Android SDK Instruction

| Version | Date | Note |
|---------|-----------|---|
| V1.001 | 2023-2-23 | First version |
| V1.002 | 2023-3-2 | Revised Unified Interface |
| V1.003 | 2023-6-9 | 1 POSPrinter add void printNormal(int iStation, byte[] bData) 2 add void printBitmap(int station,Bitmap bmp, int width, int alignment) |
| V1.0031 | 2023-7-17 | 1 modify printPDF |

Content

| | |
|---|---|
| Android SDK Instruction | 1 |
| 一、 Interface File..... | 4 |
| 二、 SDK Interface Instruction | 4 |
| 1. Printer..... | 4 |
| 1) Constructor | 4 |
| 2) Printer status value callback..... | 4 |
| 3) Open printer..... | 4 |
| 4) Close printer..... | 4 |
| 5) Cutter | 4 |
| 6) Print bitmap | 5 |
| 7) Send ESC data..... | 5 |
| 8) Print barcode..... | 6 |
| 2. Serial port..... | 6 |
| 1) Constructor | 6 |
| 2) Serial port data callback..... | 6 |
| 3) Open serial port | 6 |
| 4) Close serial port..... | 7 |
| 5) Send data..... | 7 |
| 6) Start and stop reading serial port data | 7 |
| 3. Magnetic Stripe Reader..... | 7 |
| 1) Constructor | 7 |
| 2) Magcard data callback..... | 7 |
| 3) Open magcard device..... | 7 |
| 4) Close magcard device..... | 8 |
| 5) Start to read magcard data | 8 |
| 6) Stop reading magcard data thread..... | 8 |
| 4. LCD | 8 |
| 1) Constructor | 8 |
| 2) Open LCD..... | 8 |
| 3) Close LCD..... | 9 |
| 4) Set LCD display parameter | 9 |
| 5) Clear LCD Screen | 9 |
| 6) Display string..... | 9 |
| 7) Display bitmap..... | 9 |

| | |
|------------------------------|----|
| 5. Drawer..... | 9 |
| 1) Constructor | 9 |
| 2) Open drawer device | 9 |
| 3) Close drawer device | 10 |
| 4) Open drawer | 10 |

Brief introduction

This SDK realizes the operation of printer, magnetic stripe card, cash drawer, LCD according to the methods specified in UnifiedPOS V1.141, and the printing class POSPrinter in the SDK corresponds to CHAPTER 30 POS Printer; The magnetic card class MSR in the SDK corresponds to CHAPTER 25 MSR – Magnetic Stripe Reader; The LCD class LineDisplay in the SDK corresponds to CHAPTER 22 Line Display; The cash drawer class CashDrawer in the SDK corresponds to CHAPTER 8 Cash Drawer; The serial port class is Serialport. For details about the functions implemented by each device, see SDK Interface Instruction.

一、 Interface File

```
possdk.aar store files in the libs folder under Android project  
minSdkVersion 21    targetSdkVersion 28  
dependencies add implementation fileTree(include: ['*.aar'], dir: 'libs')
```

二、 SDK Interface Instruction

1. Printer

```
import upos.POSException;  
import upos.POSPrinter;  
import upos.POSPrinterConst;  
import upos.events.StatusUpdateEvent;  
import upos.events.StatusUpdateListener;
```

1) Constructor

```
POSPrinter ()
```

2) Printer status value callback

```
void addStatusUpdateListener (StatusUpdateListener l)  
void statusUpdateOccurred(StatusUpdateEvent e);  
void removeStatusUpdateListener(StatusUpdateListener l)
```

3) Open printer

```
void open(String logicalDeviceName) throws POSException  
Parameter logicalDeviceName PTR_CP_2INCH :2inch ; PTR_CP_3INCH :3inch  
It will throw POSException(POS_FAILED) when open failed.
```

4) Close printer

```
void close()
```

5) Cutter

```
void cutPaper(int percentage)  
Parameter percentage PTR_CP_FULLLCUT: full cutting;
```

PTR_CP_PARTIALCUT: half cutting

6) Print bitmap

void printBitmap(int station, String filePath, int width, int alignment)

Parameter station ignore

filePath path of bitmap

width Print width of bitmap

| | | |
|--------------------------|---------------|--------|
| alignment alignment mode | PTR_BC_LEFT | Left |
| | PTR_BC_CENTER | Center |
| | PTR_BC_RIGHT | Right |

void printMemoryBitmap(int station, byte[] imagedata, int type, int width, int alignment)

Parameter station ignore

imagedata bitmap's data

type PTR_BMT_BMP PTR_BMT_JPEG

width bitmap's width

| | | |
|--------------------------|---------------|--------|
| alignment alignment mode | PTR_BC_LEFT | Left |
| | PTR_BC_CENTER | Center |
| | PTR_BC_RIGHT | Right |

void printBitmap(int station, Bitmap bmp, int width, int alignment)

Parameter station ignore

bmp bitmap

width bmp's width

| | | |
|--------------------------|---------------|--------|
| alignment alignment mode | PTR_BC_LEFT | Left |
| | PTR_BC_CENTER | Center |
| | PTR_BC_RIGHT | Right |

7) Send ESC data

void printNormal(int iStation, String strData)

Parameter: iStation ignore

strData ESC data

void printNormal(int iStation, byte[] bData)

Parameter: iStation ignore

bData ESC data bytes

8) Print barcode

```
void printBarCode(int station, String strData, int symbology, int height, int width, int alignment, int
textPosition)
```

Parameter station ignore

strData barcode data

symbology barcode type PTR_BCS_UPCA, PTR_BCS_UPCE...PTR_BCS_***

height barcode height 1<=height<=255

width barcode width 2<=width<=6

alignment alignment mode PTR_BC_LEFT PTR_BC_CENTER PTR_BC_RIGHT

textPosition text position PTR_BC_TEXT_NONE: not printing

PTR_BC_TEXT_ABOVE: top of barcode

PTR_BC_TEXT_BELOW: bottom of barcode

PTR_BC_TEXT_BOTH: print both top and bottom

2. Serial port

```
import upos.POSException;
import upos.Serialport;
import upos.events.DataEvent;
import upos.events.DataReceiveListener;
```

1) Constructor

Serialport ()

2) Serial port data callback

```
void addDataReceiveListener(DataReceiveListener l)
void dataReceiveOccurred(DataEvent e)
void removeDataReceiveListener(DataReceiveListener l)
```

3) Open serial port

void open(String logicalDeviceName) throws POSException

Parameter: logicalDeviceName serial port path, Baudrate eg. "/dev/ttyS1,9600"

It will throw POSException(POS_FAILED) when open failed.

4) Close serial port

```
void close()
```

5) Send data

```
void writeData(byte[] bData,int iLen)
```

Parameter: bData data to send

iLen data length

6) Start and stop reading serial port data

```
void startReadData(boolean bStart)
```

Parameter: bStart true start to read serial port thread; false stop reading data thread

Data read will be called back by listener

3. Magnetic Stripe Reader

```
import upos.POSException;
```

```
import upos.MSR;
```

```
import upos.events.DataEvent;
```

```
import upos.events.DataReceiveListener;
```

1) Constructor

```
MSR()
```

2) Magcard data callback

```
void addDataReceiveListener(DataReceiveListener l)
```

```
void dataReceiveOccurred(DataEvent e);
```

```
void removeDataReceiveListener(DataReceiveListener l)
```

3) Open magcard device

```
void open(String logicalDeviceName) throws POSException
```

Parameter logicalDeviceName ignore

It will throw POSException(POS_FAILED) when open failed.

4) Close magcard device

```
void close()
```

5) Start to read magcard data

```
void authenticateDevice(byte[] buffer)
```

Parameter: buffer ignore

Magcad data read will be called back by dataReceiveOccurred

6) Stop reading magcard data thread

```
void deauthenticateDevice(byte[] buffer)
```

Parameter: buffer ignore

4. LCD

```
import upos.POSException;
```

```
import upos.LineDispaly;
```

```
import upos.LineDisplayConst ;
```

1) Constructor

```
LineDispaly()
```

2) Open LCD

```
void open(String logicalDeviceName) throws POSException
```

```
Parameter logicalDeviceName: LINEDISPLAY_TYPE_CD6 9VFD;  
                              LINEDISPLAY_TYPE_CD9 32X144;  
                              LINEDISPLAY_TYPE_CD10 65X132;  
                              LINEDISPLAY_TYPE_CD8 24X128;  
                              LINEDISPLAY_TYPE_CD11 32X240;  
                              LINEDISPLAY_TYPE_COG 65X132COG
```

It will throw POSException(POS_FAILED) when open failed.

3) Close LCD

```
void close()
```

4) Set LCD display parameter

```
void setDescription(int iDescriptor,int iValue)
```

Parameter: iDescriptor

LINEDISPLAY_DESCRIPTOR_BACKLIGHT open and close backlight

iValue 0 close, 1 open

LINEDISPLAY_DESCRIPTOR_CONTRAST set contrast iValue 0-9

5) Clear LCD Screen

```
void clearText ()
```

6) Display string

```
void displayText(String strText,int iFontSize)
```

Parameter: strText character data

iFontSize font size

7) Display bitmap

```
void displayBitmap(String path,int iWidth,int iAlignX,int iAlignY)
```

Parameter path bitmap path; ignore other parameter

5. Drawer

```
import upos.POSException;
```

```
import upos.CashDrawer;
```

1) Constructor

```
CashDrawer ()
```

2) Open drawer device

```
void open(String logicalDeviceName) throws POSException
```

Parameter logicalDeviceName ignore

It will throw POSException(POS_FAILED) when open failed.

3) Close drawer device

```
void close()
```

4) Open drawer

```
void openDrawer ()
```