

All-in-One Fanless POS System **PTE0120**

The 3nStar All-in-One PTE0120 has been designed for Point of Sale and Hospitality applications.

It is robust, dust resistant and capable of continuous operation 24 hours a day, 365 days a year.









Features:

- 15" Capacitive Multitouch Touch Screen: Provides a brighter image and a more sensitive touch.
- Industrial Fanless Motherboard with Intel J6412: efficient, Stable, and reliable.
- 4GB RAM expandable up to 16GB.
- Solid Stage 120GB Hard Drive expandable to 1TB provides best performance, reliability and durability.
- Optional Dual Band 802.11ac, a/b/g, n Wi-Fi

- Optional Bluetooth 4.0: Easy pairing with all your devices (BT Scanners, Mobile Printers, keyboard).
- Rich I/O: 7 USB, 2 RS232, 1 VGA
- Optional Customer Display 9.7" LCD for better customer interaction
- Support PXE (Preboot Execution Environment) that allows to be configured and booted remotely by an administrator
- Compatible with most versions of Windows and Linux

Physical	
Dimensions	400mm x 360mm x 210mm
Weight	6.3Kg.
Construction	ABS Plastic and Galvanized Steel
Color	Silvery around the body
Performance	
Operating system	(Optional) Windows 7,8,10, and Linux
CPU	Intel J6412 2.0Ghz.
Memory	4GB DDR4 expandable to 16GB
Storage	120GB SSD expandable to 1TB
Connectivity	
Wi-Fi	Double Band 802.11ac, a/b/g, n (Optional)
Bluetooth	4.0 (Optional)
Ethernet	10/100/1000M RJ45
USB	7 Ports (1 dedicated for MSR)
Serial RS232	2 Ports
Cash Drawer	1 RJ12
Video Output	1 VGA Port
Touch Panel	
Touchscreen type	Capacitive 10 points
Transmittance	>95%
Touch times	More than 50,000,000
Monitor	
Resolution	1024 * 768
Pixel	0.297(V)×0.297(H)mm
Brightness (Typical)	400 cd/m ²
Contrast Ratio	800:1(Typical) 450:1(Min)
Response Time	16ms
Viewing Angle	150°/140°
Color Support	16,2M
Horizontal Frequency	60Khz.
Vertical Frequency	78Hz
Bandwidth	60Hz
Lifetime	More than 50,000 Hours
Electrical	
Adapter Output	DC 12V, 7.5A
Adapter Input	Adapter AC 100-240V, 50-60HZ

Environmental	
Operating Temperature	0°C ~ 50°C
Storage Temperature	-20°C ~ 60°C
Humidity	10% ~ 90% (without condensation)
Packaging	
In the Box	AC Adapter and Manual
Carton Size	320mm x 480 mm x 460mm
Gross Weight(kg)	9.5Kg
Certifications and Warranty	
Certifications	CE, ROHS, FCC, CCC
Warranty	1 year (Extended Warranty Available)

Accesorios:



9.7" Customer LCD Customer Display PTE0105-M10



USB Magnetic Stripe Reader 3 Tracks PTE0105-MSR



