


Android 8" Point of Sale Mobile Terminal **PTA0130**

The PTA0130 is a compact and flexible Point of Sale (POS) terminal that operates wirelessly and is powered by Android 12. It includes a 5-megapixel camera, 2GB of RAM, and 16GB of storage, making it efficient for handling basic transactions and apps.

It comes with a 58mm thermal receipt printer, allowing businesses to print receipts on-site. Its small size and affordability make it ideal for businesses with limited space, such as small retail stores or food trucks, where it can help improve transaction processing and inventory management.



Features

- Android 12
- 8" IPS LCD touch screen display
800*1280 Pixels
- Quad Core 2.0GHz
- 2GB RAM, 16GB storage and a Mini SD card slot that support up to 128GB
- 4G, Wi-Fi, BT, NFC, GPS
- 3.2" Customer Display
- Rechargeable 3000 mAh Lithium battery
- 58mm Thermal Receipt Printer
- 5MP Auto Focus Camera with built-in barcode decoding software for fast and accurate scanning

Physical	
Dimensions	271mm x 124mm x 91mm
Weight	770g.
Color	Black
Performance	
Operating system	Android 12
CPU	Qualcomm 2290 Quad Core
Memory RAM	2 GB
Storage	16 GB
Sd Card Slot	Micro SD/TF up to 128 GB
Connectivity	
Wi-Fi	Dual Band 802.11 a/b/g/n
3G	WCDMA: B1/B2/B4/B5/B8
4G	LTE FDD: B1/B2/B3/B4/B5/B7/B8/B28A LTE TDD: B38
Sim Slots	Dual Sim (Nano)
BT	2.1 EDR, 3.0 HS, 4.2 LE, 5.0 LE
GPS	GPS, BeiDou, Glonass
Interfaces	1 Type-C (OTG), 4 USB, 1 RJ45 (Ethernet), 1 RJ12 (drawer port 12V), 1 RJ11(RS232)
NFC	ISO14443 Type A/B, Mifare
Display	
Type	LCD Color
Size	8"
Resolution	800*1280 Pixels
IPS	Yes
Brightness	350cd/m(TYP)
Touch	Capacitive Multi-touch panel
Rear Customer Display	3.2" / Resolution 240 * 320 Pixel
Other I/O Devices	
Printer	Paper Roll Width/Diameter: 58mm/50mm Printing Speed: 70mm/s Printing life ≥50KM"
Camera	5MP with autofocus
Power and Battery	
Battery	Rechargeable Lithium battery 7.6V 3000mAh
Duration	Supports 600 receipts printing or 4 hours standby
Adapter Charger Input	AC 100-240V, 50-60HZ
Adapter Charger Output	9V. 2A.

Environmental

Operating Temperature	0°C ~ 40°C
Storage Temperature	-10°C ~ 50°C
Humidity	5% ~ 85% (non-condensing)
Drop Durability	1.5m

Packaging

In the Box	AC Adapter, Charger, User Manual, Paper Roll
Carton Size	307mm x 156mm x 124mm
Gross Weight	1.8Kg.

Warranty

Warranty	1 Year (Extended Warranty Available)
----------	--------------------------------------

